

Тape	Mount Type	Nominal voltage	Rated capacity(Wh)	Цена, \$
BP-C190SD	SONY V Mount	14.8V	190	425
BP-C160SD			160	380
BP-C130SD			130	295
BP-C95SD			95	255
BP-C190AD	Anton/Bauer Gold Mount		190	425
BP-C160AD			160	380
BP-C130AD			130	295
BP-C95AD			95	255

- ※ LCD display the battery capacity exactly
- ※ LCD display Cycle times
- ※ Has all advantages of traditional battery
- ※ Compatible with traditional Li-ion battery charger

Li-ion Аккумуляторы для камкордеров с LCD

Тape	Mount Type	Nominal voltage	Rated capacity(Wh)	Цена, \$
BP-C190SE	SONY V Mount	14.8V	190	380
BP-C160SE			160	315
BP-C130SE			130	280
BP-C95SE			95	255
BP-C190AE	Anton/Bauer Gold Mount		190	380
BP-C160AE			160	315
BP-C130AE			130	280
BP-C95AE			95	255

E Type Li-ion Аккумуляторы для камкордеров

Type	Mount Type	Output Voltage	Adapter Output	Цена, \$
BC-C4S	SONY V Mount	16.8V	12V 50W	275
BC-C2S				205
BC-C4A	Anton Gold Mount			275
BC-C2A				205
BC-C4N	Sony NP-1B			265
BC-C2N				195

- ※ 5 levels LED power indicator.
- ※ Has all advantages of traditional battery
- ※ Compatible with traditional Li-ion battery charger

Зарядные устройства

Type	Mount Type	Output Voltage	Adapter Output	Цена, \$
BC-C2SD	SONY V Mount	16.8V	12V 50W	280
BC-C2AD	Anton Gold Mount			280

- ※ Standard Mount: According to Anton/Bauer and SONY product, install with Gold Mount (A type Mount) or SONY V Mount, link is safe and dependable.
- ※ Fast charge system: Two batteries can be charged simultaneously, charge current is 2.0A each battery,
- ※ Provide DC power supply: As an adapter, it can offer DC 12V power supply for camcorder.
- ※ LED display working status: The indicator light glitter during charging, when the battery's capacity is full, the indicator light is bright constantly.

Адаптеры питания для камкордеров

Type	Adapt to	Цена, \$
BC-C2	Travel Charger: BC-C2 Camera battery charger can charge camera Li-ion battery of COMER or B type port.	230
AP-CA	AP-CA Camera mount can be fitted on the camera, fix Gold-Mount-battery, and offer one attachment.	45
AP-CS	AP-CS Camera mount can be fitted on the camera, fix V-Mount-battery, and offer one attachment.	45

CM-JVCA	The CM-JVCA eliminates the dependence on small consumer batteries that lack the power demanded by professionals. This specially designed adaptor supplies the proper regulated operating voltage to the GY- D101EC camera while providing the ability to use standard 12 volt video accessories such as on-camera lighting – all powered from the same high performance battery. (Use for A/B Battery)	105
CM-JVCS	The CM-JVCS eliminates the dependence on small consumer batteries that lack the power demanded by professionals. This specially designed adaptor supplies the proper regulated operating voltage to the GY- D101EC camera while providing the ability to use standard 12 volt video accessories such as on-camera lighting – all powered from the same high performance battery.(Use for SONY Battery)	105
Дополнительные аксессуары		
Type	Descriptions	Цена, \$
CM-KZ	Fixture for Ultra light to the Camcorder	15
CM-SWZ	Switcher line of which one end connecting the PACK Charger and the other connecting COMER Battery with the B type plug	10
CM-BXM	Adapter line of which one end connecting the Battery and the other connecting the camcorder	15
CM-BXT	Adapter line for connecting the Power and the Charger	7
CM-RGJ	Soft focus attachment	40
CM-LGJ	Optical Filter	40
A-GP-S	The A-GP-S is a temporary solution to allow the use of V-type batteries on 3-Stud configured cameras. It can also be used as a charge adapter, enabling you to temporarily charge V-type batteries on COMER series 3-Stud charging equipment.	115
S-GP-A	The S-GP-A is a temporary solution to allow the use of 3-Stud batteries on V-Type configured cameras. It can also be used as a charge adapter, enabling you to temporarily charge 3-Stud batteries on COMER series V-Type charging equipment.	115
CM-TS	The CM-TS Hotswap adapter mounts directly to the existing V-Type plate on the camera and allows for continuous battery operation.	150
CM-TA	The CM-TA Hotswap adapter mounts directly to the existing 3-Stud plate on the camera and allows for continuous battery operation.	150

Накамерные светильники серии Ultralight

Type	Adapt to	Wire length	Color temperature	Цена, \$
CM-168	SONY SX digital camcorder	218(mm)	3200k	95
CM-518	All camcorder receive power from Gold Mount type battery	518(mm)		

※ Ultralight can be fitted on the camcorder handle conveniently, powered by video battery directly.

※ Use OSRAM tungsten halogen lamp, lighting efficiency is high; its life is up to 5000 hours.

※ Offer diversified power, color temperature, light range and other selection.

Студийный свет

Type	Product Name and Descriptions	Цена, \$	
SOFT LIGHT SERIES	CM-SR-2*36W	Tricolor Fluorescent Light without the function of adjustable luminance. Alternative Lamp Power:36W, 55W	135
	CM-SR-4*36W		195
	CM-SR-6*36W		253
	CM-SR-2*55W		145
	CM-SR-4*55W		220
	CM-SR-6*55W		290
	CM-SRA-2*36W	Tricolor Fluorescent Light with the function of adjustable luminance Alternative Lamp Power:36W, 55W	245
			395
			550
			275
			430
			580
	CM-R-150W	Soft Light Lamp Power: 150W	45
	CM-TR-800W	Focused Soft Light Lamp Power:800W	50
CM-TR-2000W	Focused Soft Light Lamp Power: 2000W	95	
SPOT LIGHT SERIES	CM-WJ-150W	Tungsten Spot Light Lamp Power:150W	145
	CM-WJ-300W/500W	Tungsten Spot Light Lamp Power:300W, 500W	160
	CM-WJ-650W	Tungsten Spot Light Lamp Power: 650W	185
	CM-WJ-1000W	Tungsten Spot Light Lamp Power:1000W	235
	CM-WJ-2000W	Tungsten Spot Light Lamp Power:2000W	285
	CM-WJ-5000W	Tungsten Spot Light Lamp Power:5000W	715
DYSPROSIUM LIGHT SERIES	CM-DD-200W	Electronic Dysprosium Light Lamp Power: 200W	1830
	CM-DD-575W	Electronic Dysprosium Light Lamp Power:575W	2140
	CM-DD-1.2K	Electronic Dysprosium Light Lamp Power: 1.2K	3130
	CM-DD-2.5K	Electronic Dysprosium Light Lamp Power:2.5K	5600
	CM-DD-4K	Electronic Dysprosium Light Lamp Power:4K	6420
	CM-DD-6K	Electronic Dysprosium Light Lamp Power:6K	15150

Накамерные светильники LED

TYPE	INPUT	MAXIMUM LUMINOSITY	COLOR TEMPERATURE	Цена, \$
CM-LED1800	DC 6V-17V	1200lux (1m)	4500K/3200K	Call
CM-LBPS1800	DC 6V-17V	1800lvx (1m)	4500K/3200K	440
CM-LBPS900	DC 6V-17V	900lux (1m)	4500K/3200K	325
CM-LBPP900	DC 6V-17V	900lux (1m)	4500K/3200K	325
CM-LEX900	DC 6V-17V	900lux (1m)	4500K/3200K	325

Аккумуляторы для ручных камкордеров

TYPE	OUTPUT	Цена, \$
BPD-540	DC 6V-17V	90
BPL-960		90
BL-U65		250